



minimum downtime, maximum productivity

SG Revolutions are the perfect tyres for wheeled loading shovels working in tough environments day in day out. Comfortably returning up to 50% serviceable tread life, and sometimes more, than conventional tyres and fill the unique design of the SG Revolution super cushion solid tyres saves time and money by eliminating downtime from punctures and repairs. At the same time they offer the same comfortable ride as pneumatic tyres and also helps to protect the investment in your machine by absorbing shocks from rough terrain.

Distributed exclusively in Europe by ITWS, the specialists in super cushion tyre technology, the SG revolution tyres are easy to install and there is a wide choice to fit all makes and sizes of machine. Our innovative new Service Exchange programme allows you to swap your old tyres and rims for a set of new tyres and exchange rims for quick and simple installation.



SG Revolution super cushion solid tyres for wheeled loaders

SE Pattern



S2C2 DWL Pattern



C2 Pattern



S2C2 Pattern



Tyre Size	Pattern	Rim Sizes	Tyre Dimensions			Load Capacity				
			Tyre Diameter mm	Tyre Width mm	Tyre Weight kg	Steering Wheels kg	Load Wheels kg	6 km/h	10 km/h	25km/h
1200-24	SC2 & C2	8.50-24 & 9.00-24	1249	310	297	7800	9438	9438	8588	7800
1200-24	SC2 & C2	8.50-24 & 9.00-24	1180	288	258	7500	9075	9075	8250	7500
1300-24	SE	8.50-24 & 9.00-24	1300	315	327	6375	7714	7714	7013	6375
1400-24	SC3	10.00-24	1427	390	425	14000	16800	16800	15120	14000
1400-25	SC3	1000-25 & 1125-25	1427	400	415	14000	16800	16800	15120	14000
17.5-25	S2C2 DWL	1400-25	1360	460	525	8000	9860	9680	8800	8000
17.5-25	SE	1400-25	1360	460	525	8000	9860	9680	8800	8000
20.5-25	S2C2 DWL	1700-25	1450	495	762	9000	10890	10890	9900	9000
20.5-25	SE	1700-25	1475	521	800	9000	10890	10890	9900	9000
23.5-25	S2C2 DWL	19.50-25	1623	575	1084	10000	12100	12100	11000	10000
23.5-25	SE	19.50-25	1623	575	1084	10000	12100	12100	11000	10000
26.5-25	S2C2 DWL	22.00-25	1730	635	1475	15000	18150	18150	16500	15000
29.5-25	S2C2 DWL	25.00-25	1860	749	1920	22500	27000	27000	24300	22500
35.65-33	S2C2 DWL	28.00-33	2080	880	2490	26000	31200	31200	28080	26000